

## The NEW Sceptar III

8-MINUTE CALL STORAGE

CHARGED WITH MICRO-USB CABLE

EXTRA LOUD AUDIO OUTPUT (96dB)

- 6 programmable channel options
- Ruggedized with IP56 Rating
- Compatible with standard AA rechargeable or disposable batteries
- USB/AC charger included
- Optional drop-in charger available



Standard Drop-in charger



## Voice Paging Redefined.

The **NEW Sceptar III** by RadioHQ is a rugged and compact voice pager designed for Fire, EMS and Public Safety agencies. The **Sceptar III's** IP56 rating for dust resistance and ability to withstand strong jets of water, ensures reliability in the most demanding environments.

**Features of the Sceptar III** include large, ergonomically designed knobs, 8 minutes of voice storage, 96dB of audio, vibrate and/or tone alerts for incoming calls, 6 programmable channel options as well as customizable alert tones, including WAV file support.

The **Sceptar III's** functional design includes field-replaceable belt clips and volume/channel select knobs. Replaceable, low-cost parts minimize repair and maintenance costs.

The **Sceptar III** is powered by a non-proprietary, AA Ni-Cad, Ni-MH or Alkaline battery. It includes an adaptable micro USB cable that allows charging directly from a PC and an AC Wall Adapter. A wide variety of other charging options are available including DC car chargers, drop-in chargers and drop-in chargers with external speakers.

The **Sceptar III** provides the most versatile charging options in the industry today.

### SCEPTAR III SPECIFICATIONS

Frequency Range	150-175 MHz
Band-split	150-157 MHz, 157-166 MHz, 166-175 MHz
Channel Spacing	12.5KHz
Selectivity	65dB @ 12.5KHz
Modulation Accept.	3KHz @ 12.5KHz
Sensitivity	4.5 uV/m @normal position
Frequency Stability	+/- 3ppm
Spurious Rejection	55dB
Audio Output Power	250mW (10% distortion)
Audio Distortion	5%
Battery	One AA Alkaline, Ni-CAD, or Ni-MH
Battery Life	2 Days/W NiMh 2500mAH Duty Cycle 8H Days @ Qty 5, 30 second Messages Per day
Weight with battery	Approx. 140 gr.
Channel Capacity	6 channels
IP Rating	IP56
MIL STD 810G	516.7 Shock 514.7 Vibration, Annex C, Procedure 1 501.6 Temperature: -20C to +70C
Operation Temp.	-20 C + 60 C

Dealer Inquiries welcome!

**radiohq.com**

Two-Way Radio Sales & Service

413 N.E. 38th Terrace | Oklahoma City, OK 73105  
405.528.2-WAY | www.FirePagerHQ.com